

Ultra-Lok Free End Clamps

- Unique buckle hood protects lock from abrasion
- Extra thick buckle contributes to stronger clamps and extended life
- Patented Ultra-Lok design locks under full pull-up tension and is 2-3 times stronger than conventional preformed band clamps - impact has no effect on Ultra-Lok lock
- Band is cut off flush with edge of buckle hood to prevent snags and provide an extra measure of safety by eliminating sharp edges
- .030 band thickness for extra durability
- Smooth I.D. construction provides uniform, gap-free inside diameter to prevent leaks



UL 9010 Portable Electric Tool
See page 11 for details



UL 4000 Battery Operated Tool

Ultra-Lok Free End Clamps

Type 201 1/4 hardened Stainless Steel Band. Thickness .030 (.76mm)

Cat. No.	Clamp Diameter				Band Width	Length	Qty.	Weight			
	Single Wrap		Double Wrap					Bands	Lbs.	Kg.	
	In.	mm	In.	mm							
UL2030	8.0	203.2	3.8	96.5	3/4	19.05	30	762	25	5.25	2.39
UL2042	11.8	299.7	5.7	144.8	3/4	19.05	42	1067	25	7.00	3.18
UL2060	17.5	444.5	8.6	218.4	3/4	19.05	60	1524	25	10.25	4.66
UL2084	25.2	640.1	12.4	315.0	3/4	19.05	84	2134	25	14.75	6.70
UL2120	36.6	929.6	18.2	462.3	3/4	19.05	120	3048	25	20.50	9.32
UL1018	3.0	76.2			1/2	12.70	18	457	25	2.00	0.91
UL1024	5.0	127.0			1/2	12.70	24	610	25	2.75	1.25
UL1028	6.0	152.4	3.0	76.2	1/2	12.70	28	711	25	3.25	1.48
UL1032	7.0	177.8	3.5	88.9	1/2	12.70	32	813	25	3.50	1.59
UL1036	8.0	203.2	4.0	101.6	1/2	12.70	36	914	25	4.00	1.82
UL1046	11.0	279.4	5.5	139.7	1/2	12.70	46	1168	25	5.90	2.70
UL1056	14.0	355.6	7.0	177.8	1/2	12.70	56	1422	25	7.10	3.20
UL1070	18.0	457.2	9.0	228.6	1/2	12.70	70	1778	25	8.50	3.90
UL1086	22.0	558.8	11.0	279.4	1/2	12.70	86	2184	25	10.20	4.60
UL1096	25.0	635.0	12.5	317.5	1/2	12.70	96	2438	25	11.20	5.10
UL1106	28.0	711.2	14.0	355.6	1/2	12.70	106	2692	25	12.70	5.80
UL1116	31.0	787.4	15.5	393.7	1/2	12.70	116	2946	25	13.30	6.00

* 1/2" Bands require ULK910 shims fitted to UL9010 tool
* 1/2" Bands require ULK2000 shims fitted to UI4000 tool

- Fully portable battery operation
- Adjustable speed and torque
- Consistent application tensioning
- Applies both widths of Clamp*
- One person operation
- Weight 18.3 Lbs. (8.4Kgs.)
- Package Quantity 1

Ultra-Lok Free End Straps



Ultra-Lok Free End Buckles

Ultra-Lok Free End Buckles Type 201 Stainless Steel

Cat. No.	Description	Qty	Weight	
			Lbs.	Kg.
UB254	Used to form 1/2" (12.7mm) Free end Clamps	100	2.4	1.1
UB256	Used to form 3/4" (19.05mm) Free end Clamps	100	3.7	1.7